





# WALL CONTROLS




- Model CF/ILSC57W (White)  
Electronic Variable Speed Control (3 Amp)**
- Rotary dial for variable selection of fan speed and sound level
  - Positive off position
  - Fits single-gang box
  - Built-in radio noise suppressor
  - 120 VAC, 3.0 Amp capacity
  - For use with all CF/CFL/IL fans within Amp rating
  - Do not use with impedance protected motor




- Model CF/ILSC72W (White)  
Electronic Variable Speed Control (6 Amp)**
- Rotary dial for variable selection of fan speed and sound level
  - Positive on/off action
  - Fits single-gang box
  - Built-in radio noise suppressor
  - Switched wire included for additional use if desired (120 VAC, 6 Amp)
  - For use with all CF/CFL/IL fans within Amp rating
  - Do not use with impedance protected motor




- Model CF/ILSC59W (White)  
60-Minute Time Control**
- Operates continuously or for any set period up to 60 minutes
  - Fits single-gang box
  - 120 VAC, 20 Amp or 240 VAC, 10 Amp capacity
  - Also recommended for low voltage (30V Max) applications
  - For use with all CF/CFL/IL fans within Amp rating



- Model CF/ILSC75V (Ivory)  
Electronic Variable Speed Control (6 Amp)**
- 240 VAC, 6 Amp capacity
  - For use with Model IL350 Cabinet Ventilator
  - Other features same as Model 72V



- Model CF/ILSC61W (White)  
15-Minute Time Control**
- Operates for any set period up to 15 minutes (no "continuous on" position)
  - Fits single-gang box
  - 120 VAC, 20 Amp or 240 VAC, 10 Amp capacity
  - Also recommended for low voltage (30V Max) applications
  - For use with all CF/CFL/IL fans within Amp rating



- Model CF/ILSC80L10-90  
Electronic Speed Control (Internal)**
- For use with all CF fans and CFL & IL fans sizes 10 - 90
  - Metal housing
  - 3 A, 120 VAC, 60 Hz

REFERENCE	QTY.	REMARKS	Project
			Location
			Architect
			Engineer
			Contractor
			Submitted by <span style="float: right;">Date</span>